


FORTUS 3280



	ABS - M30	ABS - M30i	PC-ABS	PC	PC - ISO	Nylon 12	ASA
Sistema de impresión	FDM						
Resistencia Máxima a la Tensión (psi)	5,200	4,650	5,900	8,300	8,300	5,600	4,750
Resistencia Máxima a la Flexión (psi)	8,730	8,800	4,800	15,100	13,089	10,000	8,720
Temp. Max. De Servicio a 66 psi (°C)	96	96	110	138	133	75	98
Temp. Max. De Servicio a 264 psi (°C)	82	82	96	127	127	55	91
Porcentaje de Tensión a la Flexión (%)	4%	2-7%	6%	4.8%	4%	30%	3-9%
Ensayo de Impacto IZOD c/m (ft-lb/in)	2.4	2.4	3.7	1.4	1.6	2.5	12
Ensayo de Impacto IZOD s/m (ft-lb/in)	5.6	5.6	9	16.4	1	31	6
Modulo de Tracción (psi)	336,000	320,000	280,000	282,000	289,800	186,000	290,000
Flexible	●○○○	●○○○	●○○○	●○○○	●○○○	●●○○	●○○○
Resistente al calor	●●○○	●●○○	●●●○	●●●○	●●●○	●●○○	●●●○
Acabado	Std.	●○○○	●○○○	●●○○	●●○○	●●○○	●●○○
	Fino	●●●○	●●●○	●●●○	●●●○	●●●○	●●●○
Disponibilidad de colores	--	--	Negro	--	--	--	--

*ASA es resistente a Rayos UV, ABS-ESD7 capacidad disipativa de estática, ASB M30I cumple ISO10993, PC ISO cumple ISO10993, PC resistente a la tensión, NYLON 12 resistente a la fatiga.